




KÖKSAN
PET PACKAGING INDUSTRY CO.



PET SHEET



PET SHEET (ROLL)

RAW MATERIAL	PET (R-PET, A-PET,FLAKE, RE-GRINDING PET SHEET)
TICKNESS	150µm - 1500µm
WIDTH	200 mm - 1450 mm
LAMINATION OPTIONS	PE / EVOH / EVAHTHERMAL FILMS
DENSITY	1.33 gr/cm ³
OXYGEN PERMEABILITY	1.1735 ml/m ² day in room temprature.
TRANSPARENCY	88%
CORE DIMENSIONS	3"- 6"
PRODUCTION METHOD	Co-Extrusion, 3-Layer (A-B-A), Lamination.
COLOR OPTIONS	Clear, Black, White, Brown, Purple, Red, Yellow, Blue, Grey, Green.
SURFACE APPLICATIONS	Anti-Static, Anti Block, Antifog.
FOOD CONTACT	Full compliance with food contact regulations (FDA and EU).
CHEMICAL SPECIFICATIONS	Resistant to the acids. Not recommended for use with high alkalized solutions.
THERMOFORMING TEMPERATURE	(120 - 160 °C), forming in cooled mold.
ENVIRONMENTAL RESPONSIBILITY	In full regulations with EU standards.
PACKING OPTIONS	EAN or Barcode printing options available.