

PET Sheet

For products made of PET
(polyethylene terephthalate)
intended to come into contact with food.

www.koksan.com



PET SHEET



DETAILS	PET SHEET (ROLL)
RAW MATERIAL	PET (VIRGIN & RPET)
THICKNESS	150µm - 1500µm
WIDTH	200 mm - 1450 mm
LAMINATION OPTIONS	PET/PE, PET/EVOH/PE, PET/EVA
DENSITY	1.33 - 1.34 g/cm ³
OXYGEN PERMEABILITY	1.1735 ml/m ² day in room temperature
TRANSPARENCY	x > %85
CORE DIMENSIONS	3"- 6"
PRODUCTION METHOD	Co-Extrusion & Lamination & Mono Pet
COLOR OPTIONS	Clear, Black, White, Brown, Purple, Red, Yellow, Blue, Grey, Green
SURFACE APPLICATIONS	Anti-Static, Anti Block, Antifog, Liquid Silicone, Anti-Freeze etc
FOOD CONTACT	FDA & EFSA
CHEMICAL SPECIFICATIONS	Resistant to acids. Not recommended for use with high alkalized solutions
THERMOFORMING TEMPERATURE	(120 °C - 160 °C), forming in cooled mold
ENVIRONMENTAL RESPONSIBILITY	In full regulations with EU standards
PACKING OPTIONS	EAN or Barcode printing options available